



## SANVO SILICONE SPRAY

### Product Description

This product is a colorless and transparent silicone oil, which can be lubricated, demoulded, polished, and rust-proof by spraying a little.

It is especially suitable for demolding between the master mold and the silica gel.

It is widely used in the production and release of various plastic, rubber, glass and metal industrial products.

### Applications

widely used for electrical insulation, demoulding and damping. Dust-proof, waterproof, etc.

### Features

- Good demoulding effect
- Anti-rust
- Lubrication
- Increase plastic surface smoothness
- Convenient and durable
- Quick-drying
- Wide application range

### Typical Properties

**Composition** Dimethicone, LPG

**Specific Gravity** 0.960~0.980/cm<sup>3</sup>

**Appearance** Colorless viscous liquid

**Odour** Solvent odour

**Gas tightness (50±1℃)** Good

**Moisture** ≤0.05%

**Pressure(25℃)** 0.40~0.50

**Heat resistance** 40±2℃, 4 hours to return to room temperature can be used normally

**Cold resistance** -5±2℃, 24 hours to return to room temperature can be used normally

**Filling ratio** Max 85% of the total volume of can

**Spray Rate** ≥96%

**Shelf life** 2 years



# TECHNICAL DATA SHEET



## Instructions

Dry and clean the surface of the substrate, shake it well before use, and spray it evenly at a distance of about 20cm from the surface of the material, and then dry it with a clean dry cloth, or install an extension tube into the nozzle and spray it deep into the gap.

## Precautions

1. Do not use near flames, sparks, direct sunlight, heat and etc.
2. This product is pressure-packed.
3. Do not expose to heat beyond 50°C.
4. Do not puncture and incinerate the can.

## Disposal of waste can

Invert the can body and press the nozzle for about 2 minutes to remove the remaining liquid. If necessary, remove the nozzle completely.

## Packing/Size

Each can has a volume of 400 ml.  
12 cans are packed in a carton.